




Colour options:



Black **White**

Cat. No.	Watts	lm/W	Lumens	Colour	Beam	Length
AA-FEV-LU6*-30**	6W	83	500lm	3000K	24° / 36°	112mm
AA-FEV-LU6*-40**	6W	83	500lm	4000K	24° / 36°	112mm
AA-FEV-LU12*-30**	12W	83	1000lm	3000K	24° / 36°	220mm
AA-FEV-LU12*-40**	12W	83	1000lm	4000K	24° / 36°	220mm
AA-FEV-LU18*-30**	18W	83	1500lm	3000K	24° / 36°	328mm
AA-FEV-LU18*-40**	18W	83	1500lm	4000K	24° / 36°	328mm
AA-FEV-LU24*-30**	24W	92	2200lm	3000K	24° / 36°	436mm
AA-FEV-LU24*-40**	24W	92	2200lm	4000K	24° / 36°	436mm
AA-FEV-LU30*-30**	30W	90	2700lm	3000K	24° / 36°	543mm
AA-FEV-LU30*-40**	30W	90	2700lm	4000K	24° / 36°	543mm
AA-FEV-LU60*-30**	60W	90	5400lm	3000K	24° / 36°	1080mm
AA-FEV-LU60*-40**	60W	90	5400lm	4000K	24° / 36°	1080mm


*Add 24° / 36° for beam angle

Add suffix **W or **BLK** for White or Black finish

Triac, Dali, 0-10V dimmable options available, contact sales office for more information

CRI80 as standard, CRI90 available on request, contact sales office for more information

Line Drawing



AA-FEV-LU6

(L) 112mm Length
(W) 22mm Width
(H) 25mm Height

AA-FEV-LU12

(L) 220mm Length
(W) 22mm Width
(H) 25mm Height

AA-FEV-LU18

(L) 328mm Length
(W) 22mm Width
(H) 25mm Height

AA-FEV-LU24

(L) 436mm Length
(W) 22mm Width
(H) 25mm Height

AA-FEV-LU30


(L) 543mm Length
(W) 22mm Width
(H) 25mm Height

AA-FEV-LU60

(L) 1080mm Length
(W) 22mm Width
(H) 25mm Height

Polar Curves

18W 24° 4000K



Product Features:

- Slick and stylish, minimalistic, in-track, low glare linear luminaire
- Designed to fit in Aurora Africa 48V track
- CRI80 as standard, CRI90 available to order
- Works with surface mounted and recessed track options

Product Specification:

Installation Type	Track
Input Voltage	48V
Luminaire Materials	Aluminium
Lifetime	50,000
CRI	80 & 90
IK Rating	IK10
IP Rating	IP20
Warranty	5 Years

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.