




Lumi-Fit+™
Wattage Selectable High Efficiency
Recessed LED Downlights



Colour :

 White




Sku	Watts	lm/W	Lumens	Colour	Beam
4"					
AA-DLHWS4-30	6W / 8W / 10W / 12W / 14W	up to 125	760lm - 1800lm	3000K	90°
AA-DLHWS4-40	6W / 8W / 10W / 12W / 14W	up to 130	800lm - 1900lm	4000K	90°
6"					
AA-DLHWS6-30	9W / 11W / 14W / 17W / 22W	up to 130	1150lm - 2950lm	3000K	90°
AA-DLHWS6-40	9W / 11W / 14W / 17W / 22W	up to 140	1200lm - 3100lm	4000K	90°
8"					
AA-DLHWS8-30	14W / 18W / 22W / 26W / 30W	up to 130	2000lm - 4200lm	3000K	90°
AA-DLHWS8-40	14W / 18W / 22W / 26W / 30W	up to 140	2100lm - 4400lm	4000K	90°
10"					
AA-DLHWS10-30	26W / 30W / 33W / 36W / 38W	up to 130	3600lm - 5200lm	3000K	100°
AA-DLHWS10-40	26W / 30W / 33W / 36W / 38W	up to 140	3700lm - 5400lm	4000K	100°

Triac, Dali, 1-10V dimmable & EM options available, contact sales office for more information

Accessories

AA-DLA4	4" Surface mount accessory
AA-DLA6	6" Surface mount accessory
AA-DLA8	8" Surface mount accessory

Line Drawing



AA-DLHWS4 (4")

(H) 53mm Height
(OD) 145mm Overall (Ø)
(CO) 120-130mm Cutout (Ø)

AA-DLHWS8 (8")

(H) 53mm Height
(OD) 228mm Overall (Ø)
(CO) 200-210mm Cutout (Ø)

AA-DLHWS6 (6")


(H) 53mm Height
(OD) 190mm Overall (Ø)
(CO) 160-170mm Cutout (Ø)

AA-DLHWS10 (10")


(H) 53mm Height
(OD) 280mm Overall (Ø)
(CO) 230-260mm Cutout (Ø)

Polar Curves

30W 4000K 90°



38W 4000K 100°



Product Features:

- Designed for a variety of applications, ideal for retrofit solutions with a wide range of cutouts available
- Delivering up to 140lm/W
- Up to 100° beam angle
- Lifetime not affected by frequent switching e.g. when using occupancy controls
- Plug and play remote driver for easy installation
- Low profile fixture, ideal for installations with limited ceiling void depths
- Opal diffuser to reduce glare and for even light distribution
- 1.5kV surge protection

Product Specification:

Installation Type	Recessed
Input Voltage	220 - 240V
Luminaire Materials	Die Cast Aluminium, Polycarbonate
Lifetime	50000
CRI	80
IK Rating	IK04
IP Rating	IP54
Warranty	5 Years

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.