



**COLOUR
SELECTABLE**

Colour :




Black

SKU	Watts	lm/W	Lumens	Colour	Beam
AA-WL10-CS	10W	up to 71	670-712lm	3000K & 4000K	90°
AA-WL18-CS	18W	up to 83	1436-1498lm	3000K & 4000K	90°

*Add suffix **W** or **BLK** for White or Black finish

Line Drawing



AA-WL10-CS


(L) 150mm Length
(W) 100mm Width
(P) 92mm Projection

AA-WL18-CS

(L) 300mm Length
(W) 100mm Width
(P) 92mm Projection

Polar Curves

18W 4000K 90°



Product Features:

- Colour selectable between 3000K, 4000K and 5000K
- Delivering up to 110lm/W
- Die cast aluminium body
- Rear entry access wiring compartment allows for easy installation
- For ambient temperatures from -20° C to 45° C

Product Specification:

Installation Type	Surface Wall Mount
Input Voltage	220 - 240V
Luminaire Materials	Die Cast Aluminium
Lifetime	50000
CRI	80
IK Rating	IK07
IP Rating	IP54
Warranty	3 Years

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserve the right to alter.